

L4 ANSWER 35 OF 44 CA COPYRIGHT 2005 ACS on STN  
 AN 107:160386 CA  
 ED Entered STN: 31 Oct 1987  
 TI Additives for cement extrusion  
 IN Tanaka, Masahiko; Shiomi, Kumiko  
 PA Sanyo Chemical Industries Ltd., Japan  
 SO Jpn. Kokai Tokkyo Koho, 4 pp.  
 CODEN: JKXXAF  
 DT Patent  
 LA Japanese  
 IC ICM C04B024-22  
 ICS C04B024-38  
 CC 58-1 (Cement, Concrete, and Related Building Materials)  
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 62036055	A2	19870217	JP 1985-176237	19850809
PRAI	JP 1985-176237		19850809		

# CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
JP 62036055	ICM	C04B024-22
	ICS	C04B024-38

AB The additives comprise 50-90 weight% water soluble or water dispersible cellulose derivs. and 10-50 weight% formaldehyde-(alkyl)naphthalenesulfonic acid condensate salt and/or formaldehyde-melamine sulfonic acid salt copolymer. Cement mixts. are easily kneaded and extruded with the additives. Thus, 80 parts hydroxypropylmethyl cellulose (8300 cP) and 20 parts Na salt of formaldehyde-naphthalenesulfonic acid condensate were mixed to give an additive, which (1 part) was added to a mixture of cement 100, asbestos 20, and H2O 35 parts. The mixture was extruded for torque 80 kg/cm and no dehydration was observed in the extruded product.

ST sulfonate formaldehyde copolymer cement dispersant;  
 cellulose deriv cement dispersant;  
 melamine formaldehyde copolymer cement dispersant

IT Cement  
 (dispersants for, formaldehyde copolymer salts and cellulose derivs.)

IT Dispersing agents  
 (formaldehyde copolymer salts and cellulose derivs., for cement)

IT 50-00-0D, polymers with sulfonated melamines 108-78-1D, sulfonated, polymers with formaldehyde 9004-65-3, Hydroxypropylmethyl cellulose 9084-06-4, Formaldehyde-naphthalenesulfonic acid copolymer sodium salt

RL: USES (Uses)